



VAPPRO VCI-999 ANTI-SEIZE COMPOUND

NATO STOCK NUMBER:
8030-32-076-1179

DESCRIPTION

VAPPRO VCI-999 is a metallic silver high temperature grease made from a high VI olefinic copolymer and a finely divided thickener. This grease is fortified with V.C.I. additives that provide it with excellent lubricating properties, stability and anti-wear capabilities.

PERFORMANCE CHARACTERISTICS

VAPPRO VCI-999 is a non-gumming, non-petroleum base grease. It has no dropping point, so it will not run out of threads when heated. It sticks to the metal threads and lets joints in pipe or nuts on bolts or studs make up with less torque.

VAPPRO VCI-999 is also a high-temperature anti-friction bearing lubricant that functions in high-speed use to 450 degree F. From 600 degree F through 2100 it functions as a dry-film lubricant for heavy load and slow speed use - such as in slides or slow-revolution equipment, with the molybdenum actually plating out to prevent metal-to-metal contact and surface scuffing. It also provides reliable lubrication in boundary conditions.

VAPPRO VCI-999 when operated at high temperatures for a prolonged time interval will need to be reapplied more frequently than when operated at lower temperatures.


COMPOSITION

VAPPRO VCI-999 is an olefinic copolymer and a finely divided thickener, homogenized with V.C.I. additive fortifiers, molybdenum disulfide (in sub-micron particle size), graphite and aluminum.

APPLICATIONS

- Gaskets -Threaded Fittings
- Bushings -Compressors
- Rollers -Electric Motors
- Hoists - Regulators
- Wenches -Valve Steams
- Bearings - Chains
- Pumps - Drives
- Gears -Turbines
- Hand/Motor Operated Valves -Furnaces
- Flanges and "O" rings -Conveyors
- Control chests and head
- Man/hand hole inspection doors
- Low-speed transmission boxes
- Burner assemblies and similar applications





SPECIFICATIONS

ASTM Drop Point
Non-melt

Water Resistance
Excellent

Viscosity base SUS @210 Degree F
4800

Color
Metallic silver

Water Soluble
Water proof

Flash Point
Non-flammable

Operating Temperature Range
-30 to 2100 Degree F

Drop Point
No dropping point

Metallic Content
No lead or copper

AVAILABLE PACKAGING

18kg pail

Magna

Magna International Pte Ltd

10H, Enterprise Road,
Singapore 629834.

Tel (65) 6786-2616

Fax (65) 6785-1497

Email info@magnachem.com.sg

info@vapprovci.com

Web <http://www.vapprovci.com>

Headquarters



Regional Offices



Follow us on social media for regular updates and news.  <https://www.facebook.com/vapprovci/>
<https://www.facebook.com/MagnaInternationalPteLtd/>

The details of our products are given completely free of undertaking. Since their application lies outside our control, we cannot accept any liability for the results. User shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith.



Copyright 2018. Magna International Pte Ltd.

Magna, Vapro VCI and Vapro VBCI are registered trademarks of Magna International Pte Ltd.